

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	4841	(threshold or vt or "v.sub.t" or vtn or "v.sub.tn") near5 NMOS	US-PGPUB; USPAT	OR	OFF	2005/06/23 08:50
L2	7840	(threshold or vt or "v.sub.t" or vtn or "v.sub.tn") near5 (N adj (MOS or MOSFET or channel or type))	US-PGPUB; USPAT	OR	OFF	2005/06/23 08:50
L3	44	(1 or 2) with (bandgap or (band adj gap) or vbg or "v.sub.bg")	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:08
L4	135	(1 or 2) same (bandgap or (band adj gap) or vbg or "v.sub.bg")	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:08
L5	91	4 not 3	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:33
L6	4020	327/108,513,539,541,543,546. ccls.	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:33
L7	2359	323/313-316.ccls.	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:34
L8	1699	330/253,261.ccls.	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:34
L9	902	(6 or 7 or 8) and (1 or 2)	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:34
L10	871	9 not 4	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:35
L11	34	10 and (tail adj current\$1)	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:42
L12	1026	(1 or 2) with (sum\$6 or add\$5 or combin\$5)	US-PGPUB; USPAT	OR	OFF	2005/06/23 09:44
L13	84	10 and 12	US-PGPUB; USPAT	OR	OFF	2005/06/23 10:30
L14	942	12 not 13	US-PGPUB; USPAT	OR	OFF	2005/06/23 10:30
L15	44	14 and ((diode adj (connect\$3 or configur\$5)) near4 NMOS)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:43
L16	48	14 and ((diode adj (connect\$3 or configur\$5)) near4 (N adj (MOS or MOSFET or channel or type)))	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:44
L17	85	15 or 16	US-PGPUB; USPAT	OR	OFF	2005/06/23 10:43
L18	47	14 and composite not 17	US-PGPUB; USPAT	OR	OFF	2005/06/23 10:47
L19	754	10 not (11 or 13 or 17 or 18)	US-PGPUB; USPAT	OR	OFF	2005/06/23 10:47
L20	74	19 and (independent with (temperature\$1 or fabrication))	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:11
L21	212	19 and (variation\$1 with (temperature\$1 or fabrication))	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:12

L22	149	21 not 20	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:12
L23	65	22 and (constant near3 voltage)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:24
L24	84	22 not 23	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:40
L25	531	19 not (20 or 22)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:41
L26	2	25 and tail	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:42
L27	50	(current adj source) with ((diode adj (connect\$3 or configur\$5)) near4 NMOS)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:44
L28	77	(current adj source) with ((diode adj (connect\$3 or configur\$5)) near4 (N adj (MOS or MOSFET or channel or type)))	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:44
L29	1	25 and (27 or 28)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:46
L30	22	(6 or 7 or 8) and (27 or 28)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:52
L31	528	25 not (26 or 29)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:56
L32	120	31 and temperature	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:57
L33	197	31 and (fabrication or manufactur\$3)	US-PGPUB; USPAT	OR	OFF	2005/06/23 11:57
L34	58	32 and 33	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:10
L35	62	32 not 34	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:23
L36	139	33 not 34	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:42
L37	269	31 not (32 or 33)	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:42
L38	113	37 and differential	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:56
L39	16	37 and comparator not 38	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:58
L40	140	37 not (38 or 39)	US-PGPUB; USPAT	OR	OFF	2005/06/23 12:59